



MONTAGE

- BOOOM 10/20/32/50 AL/BR, lighter than 2 kg -
- Plastic Ceiling Plate (Standard) -

1. Mount the screw hook (A) in the ceiling.
2. Route the electricity cable through the ceiling cap (D).
- 3a. Determine the height of the lamp and, if necessary, shorten the electric cable (F). The standard supplied length is 180 cm. A longer cable length is possible upon request.
- 3b. How to shorten the electric cable?
 - Determine the desired length.
 - Cut the cord, strip the sheath
 - Strip the wires to a length of about 8 mm.
4. Route the electricity cable through the first hole of the strain relief (C), then route it from the same side through the second hole. Make sure you leave a few centimeters at the end of the wire.
5. Hang the strain relief (C) on the screw hook (A).
6. Connect the electricity to the luster terminal (B). Connect each wire that comes from the lamp to the same color wire that comes from the ceiling.
7. Move the ceiling cap (D) against the ceiling and ensure that the other parts disappear under the cap.
8. Now turn the screw (E) through the ceiling cap (D) so that it stays in place.
9. Enjoy the light.



BOOOM!

GENERAL INFORMATION


- Fitting E27, max. 40 W
- Beware of sharp edges
- Only for indoor use
- Not suitable for wet areas
- Light bulb not included

By Marc de Groot
Joris van den Berghweg 103 - B 0.03
1067 HP Amsterdam
The Netherlands


info@bymarcdegroot.com
www.bymarcdegroot.com




COMPONENTS



- (A) Screw hook (not included)
- (B) Luster terminal (not included)
- (C) Strain relief
- (D) Ceiling cap
- (E) Screw
- (F) Electricity cable and fixture



Always switch off the power before starting the installation.



MONTAGE